

## Colour Edging Pen 243 Technical Data Sheet 2008

### 1. USES

- For the opaque dyeing of closed surfaces in the wood, plastic and metal sector.
- For a quick uncomplicated dyeing of corners, edges and grooves.
- To varnish mitre grooves on foiled-covered UPVC window profiles and doors.
- For indoor and outdoor use.

### 2. PROPERTIES

- Pigmented covering lacquer based on acryl.
- Fast-drying.
- High opacity.
- Can be lacquered over with all Touch-Up and Aerosol lacquers.
- Good adhesion to many lacquer, plastic and metallic surfaces (not to soft-UPVC).
- Good light fastness and weather-resistance (adequate coat thickness required!).
- If being applied properly the lacquer quality applies 2 years to the requirements of the VOB.

### 3. PROCESSING INSTRUCTIONS

- Shake pen well for at least 10 seconds. - ball agitators must be audible. Take off cap, hold pen upside down and briefly de-aerate by pressing with thumb and forefinger on the lower part of the housing (pressure adjusting is audible). Hold pen with tip pointing downwards and press slightly until tip is soaked with dye. Touch-up with rapid strokes. For exterior use, the lacquer coats have to be stronger. When working on windows and doors, do not use in the sealing area. If lacquer ceases to flow well, press again. Replace cap after use areas to be treated have to be free from dust, grease and silicone. Dried-up tips to be washed out in nitrocellulose thinner. If pen has not been used for a long time or where pigment separates at the tip just replace with a new tip (spare tip in the pen's bottom). For further information please see instructions for use.

### 4. SPECIFICATIONS

- **Dust-dry:** after approx. 1-2 minutes
- **Dries to the touch:** in approx. 2-5 minutes (dependent on room temperature and coat thickness).
- **Lightfastness:** good.
- **Weather resistance :** good.
- **Shelf life:** at least 2 years (if stored in original receptacle and at room temperature).

### 5. INFORMATION ON SAFE USE / SAFETY INSTRUCTIONS

- Highly flammable.
- Irritant.
- Keep away from sources of ignition. - No smoking.
- Do not breathe vapour.
- Use in well ventilated areas, only.
- Keep out of reach of children.

### 6. DISPOSAL INSTRUCTIONS

- Do not allow product to enter drains or watercourses.
- Receptacles to be added to the household waste, only when completely emptied and dried up.
- Material remainders to be disposed of according to the European Waste Disposal regulation no. AAV 080111 - *dye and lacquer waste containing organic solvents or other dangerous goods*.
- For detailed information please refer to our Material Safety Data Sheet or ask your local waste industry office.

### 7. AVAILABLE

- Single pen
- Assortment of 5
- Assortment of 10
- Standard and special colour shades
- Spare tips - unit of 10

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).